

Document type	Technical Data Sheet
Name	MOROCCAN OLIVE SOAP
Description	This traditional Moroccan olive oil soap is well-known for its amber colour and intense olive oil scent. Its main property is to give a light protection from liquid and dirt to TADELAKT.
Composition	Water, olive oil, sodium carbonate.
Versions	LIGHT, DARK
Appearance	Thick cream
Colour	The dark version is dark amber, the light version is light amber
Packaging	1 kg polyethylene packaging; 500 g polyethylene packaging
Application	By hand, using a sponge or soft cloth
Where to use it	It is the traditional protective for the TADELAKT, but it can also find an interesting use as a finish for the BETON STUCCO, to which it gives special aesthetic effects. It can be used on interior and exterior finishes.
Dilution	Dilute 1 part of product with 5 parts of water (in weight)
Consumption	2 g/sqm of non-diluted product. 10 g/sqm of diluted product
Drying	1 hour to the touch, 16 hours in depth, at 20°C
Application temperatures	min 8 max 40°C – R.U. < 85% ca
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/l): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Shelf life	36 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	It is important to adhere to the prevailing safety and hygiene standards while using it. Always keep the product out of reach of children. In the event of ingestion seek medical assistance without delay and present the container or label.
Disposal	Product must be disposed of according to norms and regulations in force.
Application Instructions	On light colour finishes, use the LIGHT version, and on dark tone finishes, use the DARK version. Dilute 1:5 with water. For optimal results as a dirt and water repellent, it is recommended to apply the solution 24 hours after the stucco has been applied. You can use a sponge, cloth, or brush for application. Ensure that you apply a very thin layer of the diluted soap solution evenly over the entire surface. Before the solution dries completely or immediately after, gently wipe off any excess soap using a soft cloth. This soap can also be used to protect BETON STUCCO or other lime-based plaster when experimenting with special effects. For example, try using MOROCCAN OLIVE SOAP DARK on BETON STUCCO GREY.
Tools	Sponge, cloth, or brush. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product.